



Unique Design



MODA-Frame

When Light Meets Style

A specially designed framing system maximizes the benefits of the MODA in a 2, 3 or 4 configuration.

This **classy recessed spotlight** delivers pure quality light based on the latest Bridgelux technology.

MODA-Frame is simple to install. It fits easily into ceiling installations with square cut-out and a height of no more than 136mm.

MODA-Frame is connected via a constant current LED driver and has a beam angle of 16°.

BENEFITS

Highly efficient LED module, >560 lm.

Uncompromising standards of design.

Saves up to 80% energy.

CRI > 80 with WW LED.

High quality material.

Special adjustment in all directions.




Dark light source with round edges and no glare.

APPLICATIONS

Residential or commercial.

Suitable for homes, offices, stores buildings, museums... and more.

MODA-Frame

MODEL NR.	MO-FR-5600 MO-FR-3000	MO-FR-2	MO-FR-3	MO-FR-4
				
LED TYPE	Bridgelux ES CW BXRA-C0603 WW BXRA-W0401			
POWER	1*10W	2*10W	3*10W	4*10W
INPUT CURRENT	CW DC 350mA WW DC 1050mA			
LED COLOR OPTION	CW 5600K 65 CRI WW 3000K 82 CRI			
TYPICAL LED LUMINOUS	CW 750 lm 29.7 Vf WW 560 lm 9.9 Vf			
MATERIAL	Aluminium	Aluminium	Aluminium	Aluminium
CUT-OUT SIZE		236mm*123mm	345mm*123mm	454mm*123mm
				
HOUSING		Matt White	Matt White	Matt White
DRIVER	LD-60V-18W-350 (CW) per fixture LD-9V-1050 (WW) per fixture			
BEAM ANGLE	16°			
	