



It's a New Moda in Town



MODA-Single

Multi Adjustment Architectural Style

This classy recessed spotlight delivers pure quality light based on the latest Bridgelux technology.

MODA-Single is easy and simple to install. It fits easily into ceiling installations with a round or square cut-out and a height of no more than 136mm.

MODA-Single is connected via constant current LED driver and has a beam angle of 16°.

MODA-Single has a dark light source with round edges and no glare.

BENEFITS

Highly efficient LED module, >560 lm.

Uncompromising standards of design.

Saves up to 80% energy.

CRI > 80 with WW LED.

High quality material.

Special adjustment in all directions.

APPLICATIONS

Residential or commercial.

Suitable for homes, offices, stores buildings, museums... and more.

MODA-Single

MODEL NR. MO-SQ-5600
MO-SQ-3000



MO-RD-5600
MO-RD-3000



LED TYPE Bridgelux ES
CW BXRA-C0603
WW BXRA-W0401

Bridgelux ES
CW BXRA-C0603
WW BXRA-W0401

POWER 1*10W

1*10W

INPUT CURRENT CW DC 350mA
WW DC 1050mA

CW DC 350mA
WW DC 1050mA

LED COLOR OPTION CW 5600K 65 CRI
WW 3000K 82 CRI

CW 5600K 65 CRI
WW 3000K 82 CRI

TYPICAL LED LUMINOUS CW 750 lm 29.7 Vf
WW 560 lm 9.9 Vf

CW 750 lm 29.7 Vf
WW 560 lm 9.9 Vf



MATERIAL Aluminium

Aluminium

CUT-OUT Diameter 118mm

118mm*118mm

SIZE



HOUSING Matt white

Matt white

DRIVER LD-12V-3W-350 (CW)
LD-9V-1050 (WW)

LD-12V-3W-350 (CW)
LD-9V-1050 (WW)

BEAM ANGLE 16°

16°

