



Quality of Light



The True Alternative for MR16 Fixtures

Stylish design with low profile cut-out.

High output, versatile fittings for different applications.

The PLANO range is connected via a constant current LED driver and has a beam angle of 24°.

Based on Bridgelux latest LED technology.

Fixed spotlight with optional 10 different reflectors attached with a SNAP-ON TECHNOLOGY.

Adjustable spotlight with asymmetric reflector.

BENEFITS

Highly efficient LED module, >560 lm.

Different fitting frame shapes produce different light effects.

Specially designed heatsink ensures LED lifetime.

Outstanding efficacy compared to halogen lamps.

High CRI > 80 with WW LED.

APPLICATIONS

Residential or commercial.

Suitable for homes, offices, stores buildings, museums... and more.

MODEL NR. PL-AD-5600
PL-AD-3000



PL-FX-5600
PL-FX-3000



LED TYPE Bridgelux ES
CW BXRA-C0603
WW BXRA-W0401

Bridgelux ES
CW BXRA-C0603
WW BXRA-W0401

POWER 1*10W

1*10W

INPUT CURRENT CW DC 350mA,
WW DC 1050mA

CW DC 350mA,
WW DC 1050mA

LED COLOR OPTION CW 5600K 65 CRI
WW 3000K 82 CRI

CW 5600K 65 CRI
WW 3000K 82 CRI

TYPICAL LED LUMINOUS CW 750 lm 29.7 Vf
WW 560 lm 9.9 Vf

CW 750 lm 29.7 Vf
WW 560 lm 9.9 Vf



MATERIAL Aluminium

Aluminium

CUT-OUT Diameter 76mm

Diameter 76mm

SIZE



HOUSING Matt white

Matt white

DRIVER LD-60V-18W-350 (CW)
LD-9V-1050 (WW)

LD-60V-18W-350 (CW)
LD-9V-1050 (WW)

BEAM ANGLE 24°

24°

REFLECTORS Asymetric

