



Sopra



The Best Solution for Ceiling Installations



Latest LED Technology for Consistant Light Output

Highly efficient downlights with two size options and energy savings of up to 50% with CFL.

Recessed downlight with a stylish design for ceiling installations.

The SOPRA range is simple to install with two high quality clips, that fit easily into ceiling installations.

The SOPRA range has a beam angle of 50° and is connected via a constant current LED driver.

Based on Cree or Bridgelux LED COB (Chip On Board) Technology. High quality aluminium reflector delivers more than 90% light output.

BENEFITS

Highly efficient LED module 850-1850 lm.

Specially designed heatsink ensures LED lifetime.

High CRI >80 with WW LEDs.

Uniquely designed housing for anti glare light output.

APPLICATIONS

Residential or commercial.

Suitable for homes, offices, stores, buildings, museums... and more.



MODEL NR. SO-11-5600
SO-11-3000



SO-21-5600
SO-21-3000



LED TYPE Bridgelux ES
CW BXRA-C1202
WW BXRA-W0802

Bridgelux ES
CW BXRA-C2002
WW BXRA-W1202

POWER 1*11W

1*21W

INPUT CURRENT DC 1050mA

DC 1400mA

LED COLOR OPTION CW 5600K 65 CRI
WW 3000K 82 CRI

CW 5600K 65 CRI
WW 3000K 82 CRI

TYPICAL LED LUMINOUS CW 1200 lm 12.8 Vf
WW 850 lm 12.2 Vf

CW 1850 lm 16.1 Vf
WW 1360 lm 15.4 Vf



MATERIAL Die-cast Aluminium

Die-cast Aluminium

CUT-OUT Diameter 118mm

Diameter 145mm

SIZE



HOUSING Matt white

Matt white

DRIVER LD-24V-20W-1050

LD-24V-33W-1400

BEAM ANGLE 50°

50°

